

No:10 PK:34940 Tuzla - İstanbul / TURKEY

### Branch

Üniversiteler Mah. 1596 Cad. Hacettepe Teknokent 5. Ar-Ge No: 8B 3. Kat Ofis No: 14 PK: 06800 Çankaya - Ankara / TURKEY

Sanayi Mah. Teknopark Bulv. Teknopark Istanbul No:1/5A Daire: Z07 PK: 34906 Pendik - İstanbul / TURKEY

(1) +90 216 527 62 22 (4) +90 216 527 62 21

@ info@armelsan.com

3.000m WORK CLASS ROV





New generation hybrid ROV System with electric thrusters



Twice as efficient as older generation hydraulic ROV's



Smaller size, higher power



Lower down time



API S53 Compliant System





# **Vehicle Specifications**

Weight in Air	3.500 kg
Dimensions (LxHxW)	3.2m x 1.9m x 1.7m
Operating Depth	3.000m
Payload	350 kg



ROV/HPU Power Input	440VAC, 120 kW 3 phase
Thrusters	7x Electric (190kgf thrust each) (4 Horizontal, 3 Vertical)
HPU	75 kW Dual Pump (1x Manipulators, 1x Tooling)

### **Hydraulic Power Unit**

Valve Packs	Sub-Atlantic Proportional Valve Pack Sub-Atlantic Selenoiadal Valve Pack (Optional RCU Valve Pack)
High Flow Supply	60+ gal/min @ 5.000 psi (API 53 Compliant)
Low Flow Supply	0 – 9 gal/min @ 3.000 psi



Cameras	1 x HD Camera 1 x SD Camera
	1 x Focus Zoom Camera
	1 x Low Light Camera
	1 x Rear Camera
	1 x Tether Camera
Lighting	6 x 25.000 Lumen (Dimmable)



# **Vehicle Equipments and Control**

Manipulators	1 x Schilling T4 1 x Schilling Rigmaster
Sonar	Tritech Super SeaKing
Pan and Tilt	2 x Pan Tilt Unit
Depth and Altitude	Valeport VA500
Navigation	RTS Nemo (INS & DVL) ARMELSAN Navigation Sensor Pack
Oto-Functions	Auto Heading Auto Depth Auto Altitude



